

# Index

## Numerics

- 10Base2, 6, 127, 130
- 10Base5, 130
- 10BaseF, 131
- 10BaseFB, 131
- 10BaseFL, 131
- 10BaseFP, 131
- 10BaseT, 6, 130
  - hubs and, 140
  - throughput, 60
- 10 Gigabit Ethernet, 146–149
  - signaling standards for, 146
- 100BaseFx, 6
- 100BaseT
  - Gigabit Ethernet and, 146
  - hubs and, 140
- 100VG-AnyLAN, 132
- 10/100 hubs, 140
- 1000BaseT, 146
- 5-4-3 Repeater rule, 139
- 80d5 format, 142
- 80/20 rule, 68
  - distribution level, 83
- 802.1d (Spanning Tree), 61
- 802.1Q (VLAN Tagging), 105, 111, 152
- 802.2 LLC sublayer, 134
- 802.3 (Ethernet), 132–136, 144, 165
  - full-duplex mode, 138
- 802.5 (Token Ring), 141, 145, 165
- 802.11, 155, 157
  - 802.11a/802.11b, 157

## A

- ABR (Area Border Router), 197
- ABR (Available Bit Rate), 151
- access level, 85, 114
  - augmenting with hubs, 128
- accounting management, 275
- Address Resolution Protocol (see ARP)
- addresses
  - broadcast, 135
  - globally unique, 234
  - IP, 170–175, 182–191
    - classes, 173–175
    - default gateways, 190
    - flexibility, 189
    - loopbacks, 188
    - for OSPF, 224
    - ranges, 184–187
    - standard subnet masks, 187–189
    - unregistered addresses, 182
  - IPv6, 322–325
    - allocations, 324
  - IPX, 242–244
  - MAC, 54, 132, 135
    - broadcast/multicast, 135
    - DECNET protocol, 135
    - Ethernet, 135
    - fault recovery and, 27
    - IP ARP packets and, 48
    - security and, 99
    - updating, 63

We'd like to hear your suggestions for improving our indexes. Send email to [index@oreilly.com](mailto:index@oreilly.com).

- addresses (*continued*)
  - multicast, 135
    - (see also addressing, multicast)
    - (see also addressing, dynamic multicast; IP multicast networks)
- addressing
  - dynamic multicast, 309
  - multicast, 307
    - anycast and, 329–331
    - IPv6 allocation, 324
- AF (Assured Forwarding), 261
  - classes, 262
  - design considerations, 270
  - Drop Precedence, 262
  - DSCP and, 265
- algorithms
  - Distance Vector, 197, 207, 236
  - DUAL, 206
  - dynamic routing protocols and, 194
  - Fair Queuing, 259
  - Link State, 213, 236
  - Priority Queuing, 260
  - Split Horizon, 205
    - Split Horizon with Poisoned Reverse, 208
  - Weighted Fair Queuing, 259
- anycast, 330
- API (Application Program Interface), QoS
  - classes and, 268
- Apple Ethernet protocol reserved type, 133
- AppleTalk, 169
- application control, filtering for, 94
- application layer (OSI model), 9
- Application Programming Interface (API), QoS classes and, 268
- architectural problems in network management, 290–298
- Area Border Router (ABR), 197
- ARP (Address Resolution Protocol), 175
  - ATMARP, 152
  - cache, 98
  - packets, 136
  - proxy, 25
  - switching vs. routing, 79
- AS (Autonomous System), 196, 215
  - BGP and, 229
  - EIGRP and, 211
  - NLSP and, 239
  - RIP and, 197–206
    - (see also OSPF Autonomous Systems; RIP)
- AS numbers, BGP and, 231

- ASBR (Autonomous System Boundary Router), 197
  - BGP and, 230
  - OSPF and, 218, 222
- Assured Forwarding (see AF)
- Asynchronous Transfer Mode (see ATM)
- ATM (Asynchronous Transfer Mode), 6, 149–154
  - ATMARP, 152
  - bottlenecks and, 253
  - collapsed backbones, 71
  - cost efficiency, 149
  - LAN services, 151–154
  - on large-scale LANs, 149
  - routing and, 11
  - telephony and, 149
  - WANs and, 149
- Attachment Unit Interface (AUI), 140
- AUI (Attachment Unit Interface), 140
- autoconfiguration, IPv6, 327–328
- Autonomous System Boundary Router (see ASBR)
- Autonomous System (see AS)
- Available Bit Rate (ABR), 151

## B

- backbone routers, 219
- backbones, 70
  - collapsed, 70–74
    - capacity, 72
    - cost efficiency, 72
    - redundancy, 73
  - distributed, 74–78
    - trunk capacity, 75–77
    - trunk fault tolerance, 77
  - Gigabit Ethernet as, 148
- backoff interval, 137
- Backup Designated Router (BDR), 216
- backups, 19
  - automatic, 24–30
    - via load balancing, 28–30
  - network management and, 274, 296
  - Spanning Tree, 63–65
    - (see also fault recovery, automated)
  - distributed backbones, 78
- bandwidth, 3, 16, 254
  - latency and, 255
- Banyan Network Operating System Ethernet types, 133
- Banyan Vines VIP, 169
- baseband signaling, 131
- Basic Service Set (BSS), 156

BDR (Backup Designated Router), 216  
 beacon frame, 143  
 Best Efforts Delivery, 256  
     FIFO compared to, 257  
     Weighted Fair Queuing and, 259  
 BGMP (Border Gateway Multicast Protocol), 315  
 BGP (Border Gateway Protocol), 228–233  
     Autonomous System numbers, 231  
     dynamic routing capabilities in  
         firewalls, 294  
     where to use, 232  
 BIA (burned-in address), 132, 135  
 blocking ports, 62  
 Bluetooth, 155, 157  
 Border Gateway Multicast Protocol  
     (BGMP), 315  
 Border Gateway Protocol (see BGP)  
 border routers, 213  
 bottlenecks  
     collapsed backbones, 72  
     efficiency and, 252  
     (see also congestion)  
 bridges  
     design issues, 139  
     (see also bridging; switching)  
 bridging  
     Ethernet to Token Ring, 11  
     root bridges, 62  
     routing vs., 10–12  
     source-route, 145  
     stability and, 51  
     (see also switching)  
 broadband signaling, 131  
 broadcast, 54  
     address, 135  
     all-subnets, 180  
     domains, 85, 169  
     multiple subnet, 179–181  
     storms, 48, 98  
     switching strategies and, 96–98  
 Broadcast and Unknown Server (BUS), 153  
 BSS (Basic Service Set), 156  
 buffering, 258–261, 266  
     monitoring statistics about, 286  
 buffers, 16  
     congestion and, 46  
 bugs in routers/switches, 48  
     (see also troubleshooting)  
 burned-in address (see BIA)  
 BUS (Broadcast and Unknown Server), 153  
 bus topology, 54

business requirements, 1–4, 16  
     bandwidth (see bandwidth)  
     expenses, 2  
     geography, 2  
     installed base, 3  
     security (see security)  
     vs. technical requirements, 1

## C

cables  
     cable plants, 57  
     Categories 3 and 5, 57, 130, 163  
         Enhanced Category 5, 163  
     Categories 6 and 7, 163  
     fiber optic, 131  
         Fast Ethernet/Gigabit Ethernet, 146  
         single mode/multimode, 167  
     Type 3, Token Ring, 6  
     (see also cabling, structured)  
 cabling, structured, 162–168  
     horizontal, 163–166  
     vertical, 166  
 caches, ARP, 98  
 capacity planning, 275  
 Carrier Sense Multiple Access/Collision  
     Avoidance (CSMA/CA), 155  
 Carrier Sense Multiple Access/Collision  
     Detection (CSMA/CD), 54  
 carrier sense phase (Ethernet), 136  
 CAU (Controlled Access Unit), 145  
 cells (ATM), 150  
 CIDR (Classless Inter-Domain  
     Routing), 174, 229  
     multiple subnet broadcast, 181  
 circuits, point-to-point, 6  
 Citrix systems, QoS classes and, 267  
 Class A–D networks, 173, 180  
 Class of Service (CoS), Ethernet and, 148  
 Classical IP, 152  
 Classless Inter-Domain Routing (see CIDR)  
 classless routing, 228  
 collapsed backbones, 70–74  
     capacity, 72  
     cost efficiency, 72  
     redundancy, 73  
 collision  
     detection  
         Ethernet, 136–138  
         full-duplex access and, 137  
         late collision, 137  
     rates, 59, 60  
     wireless LANs, 155

- complexity
  - redundancy, implementing, 23
  - traffic anomalies and, 47
- configuration management, 273
  - tracking physical changes, 274
- congestion, 45
  - efficiency and, 252
  - hop counts and, 250
  - RED and, 252
  - RIP, 238
  - routers and, 86
  - SAP, 238
  - (see also bottlenecks)
- console ports, management problems
  - with, 305
- containment, 48
- Controlled Access Unit (CAU), 145
- core level, 85
- core links, oversubscribing, 252
- CoS (Class of Service), Ethernet and, 148
- cost efficiency, 2, 247
  - ATM, 149
  - collapsed backbones, 72
  - failures and, 15
  - Gigabit Ethernet on desktops, 147
  - hierarchical design, 82
  - horizontal cabling, 164
  - installed base, 129
  - LAN technologies, 126–129
  - manageability and, 12
  - performance and, 16, 127
  - redundancy and, 42
  - switching vs. routing, 80
  - Token Ring, 144
  - trunks, 109
  - VLANs, 66
  - (see also efficiency)
- cost-to-bandwidth ratios, ATM, 149
- CRC errors, 250
- CSMA/CA (Carrier Sense Multiple Access/Collision Avoidance), 155
- CSMA/CD (Carrier Sense Multiple Access/Collision Detection), 54
- CSU/DSU devices, out-of-band management of, 298

## D

- data link layer (OSI model), 6
  - LLC sublayer, 134
  - network congestion and, 47
- Data Link Switching (see DLSw)

- DECNET protocol, 135, 169
  - TCP/IP operating with, 135
- design
  - bridges/hubs/switches, 139
  - constraints
    - expenses, 2
    - installed base and, 3
  - efficiency and, 248, 270–272
  - goals, 51
  - hierarchical, 81–113
    - cost efficiency, 82
    - hop counts and, 249
    - OSPF Autonomous Systems, 222
    - routing strategies, 83–95
    - switching and bridging
      - strategies, 95–100
    - VLAN-based topologies, 100–113
  - human errors in, 51–54
  - limiting, 49
  - IP multicast networks, 315–318
    - multicast administrative
      - zones, 316–318
    - QoS and, 318
  - management considerations, 275–280
    - ease of access, 277
    - equipment, location of, 279
    - probes, location of, 275
  - reliability, implementing, 113–115
  - strategies
    - for IP, 182–191
    - for IPX, 242–246
  - switching vs. routing
    - modern style, 80
    - old style, 78–80
  - top-down philosophy, 12
  - (see also design types)
- design types, 50–125
  - concepts, 50–58
  - LAN topologies, large-scale, 115–125
    - core-level routers, 116–118
    - dedicated network-management
      - VLANs, 276
    - distribution-level routers, 118
    - multilevel routers, 119
    - remote sites, connecting, 121–124
  - topologies, 54–58
    - bus, 54
    - mesh, 57
    - ring, 55
    - scalability of, 58–61
    - star, 56

- token bus, 54
    - (see also design types, LAN topologies, large-scale)
  - Designated Router (DR), 216
  - devices
    - BIAs and, 135
    - collision detection and, 136–138
    - connecting, 114
    - efficient use of, 248
    - end, 51
      - bridging/switching and, 96
      - broadcasts and, 96
      - connections, 81
      - cost efficiency and, 127
      - DHCP and, 289
      - dynamic routing protocols and, 54, 65
      - HSRP and, 65
      - hubs and, 139
      - network functions, performing, 25, 52
      - reliability and, 53, 114
      - routing and, 25
      - stability and, 51
      - traffic and, 83
      - VLANs and, 110
      - VRRP, 65
    - network, 51, 53
      - automated fault recovery and, 26
      - design philosophy and, 13
      - Ethernet framing standards, 132
      - redundancy and, 18
      - stability, 31
    - number of per Ethernet segment, 59
    - out-of-band management of, 298
      - CSU/DSU devices, 298
      - nonstandard devices, 302
    - serial, inverse terminal servers, polling with, 303
    - Spanning Tree and, 63–65
  - DF (Don't Fragment) bit, 251
  - DHCP (Dynamic Host Configuration Protocol), 191
    - end devices, managing, 289
    - network-management problems with, 289
  - Differentiated Services, 261–263
    - design considerations, 270
  - diffserv (see Differentiated Services)
  - Diffusing Update Algorithm (DUAL), 206
  - Digital Subscriber Line (DSL), 9
  - Distance Vector algorithm, 197, 207, 236
  - Distance Vector Multicast Routing Protocol (DVMRP), 314
  - distributed backbones, 74–78
    - trunk capacity, 75–77
    - trunk fault tolerance, 77
  - Distributed Services Control Point (see DSCP)
  - distribution
    - areas, 110–113
      - network-management VLANs and, 276
      - sizing, 112
    - level, 85
      - 80/20 rule, 83
    - switches, 114
  - DLSw (Data Link Switching), 251
    - tunnel protocol, 142
  - DNS (Domain Name Service), 191
    - servers, linking to DHCP servers, 289
  - Domain Name Service (see DNS)
  - Don't Fragment (DF) bit, 251
  - double-ring topology, 55
  - DR (Designated Router), 216
  - DSCP (Distributed Services Control Point), 261, 263–265
    - AF and EF values, 265
  - DSL (Digital Subscriber Line), 9
  - DUAL (Diffusing Update Algorithm), 206
  - duplicating equipment, 19
  - DVMRP (Distance Vector Multicast Routing Protocol), 314
  - Dynamic Host Configuration Protocol (see DHCP)
  - dynamic routing protocols
    - end devices and, 53
    - fault recovery, automated, 65
    - IPX, 236–242
      - RIP and SAP, 236–238
    - types of, 196
      - (see also IP dynamic routing; OSPF; RIP)
- ## E
- Early Token Release (ETR), 143
  - EF (Expedited Forwarding), 261
    - design considerations, 270
    - DSCP and, 265
    - traffic shaping, 266
    - VLL and, 263
  - efficiency, 247–272
    - bottlenecks and congestion, 252
    - buffering and queuing, 258–261
    - equipment features and, 248
    - filtering and, 253

efficiency (*continued*)

- hop counts and, 249
- MTU and, 250–252
- QoS and, 256–258
  - design considerations, 270–272
  - DSCP and TOS, 263–265
  - Integrated and Differentiated Services, 261–263
  - Layers 2 and 3, 258
  - RSVP and, 269
- queuing
  - Fair Queuing, 259
  - FIFO, 259
  - Priority Queuing, 260
  - Weighted Fair Queuing, 259
- traffic
  - defining types, 267–268
  - shaping, 265
  - (see also cost efficiency)
- EGP (Exterior Gateway Protocol), 196, 223, 228
- EIGRP (Enhanced Interior Gateway Routing Protocol), 84, 206–213
  - active and stuck-in-active routes, 210
  - functionality, 207–210
  - interconnecting autonomous systems, 211
  - IPX on, 238
  - redistributing with other routing protocols, 213
- ELANs (Emulated LANs), 152
- Emulated LANs (ELANs), 152
- encryption, 8, 275
  - WEP and, 158
- end devices
  - bridging/switching and, 96
  - broadcasts and, 96
  - connections, 81
  - cost efficiency and, 127
  - DHCP and, 289
  - dynamic routing protocols and, 54, 65
  - HSRP and, 65
  - hubs and, 139
  - network functions, performing, 25, 52
  - reliability and, 53, 114
  - routing and, 25
  - stability and, 51
  - traffic and, 83
  - VLANs and, 110
  - VRRP and, 65
- Enhanced Interior Gateway Routing Protocol (see EIGRP)

equal-cost multipath routing, 210, 215, 253

- EIGRP and, 238
- NLSP and, 241
- equipment
  - dedicated management, location of, 279
  - efficient use of, 248
- errors
  - CRC, 250
  - ICMP and, 176
- ESS (Extended Service Set), 156
- Ethernet, 6, 130–141
  - ATM compared to, 153
  - backoff interval, 137
  - bridges/hubs/switches, 139
  - carrier sense phase, 136
  - collapsed backbones, 74
  - collision
    - detection, 136–138
    - rates, 59
  - congestion and, 47
  - cost efficiency, 126
  - framing standards, 132–136
    - addresses, 135
  - IEEE 802.2/802.3, 7
  - jamming pattern, 137
  - MTU default, 250
  - physical implementations, 130
  - protocol types, 133
  - QoS and, 258
  - routing IP to Token Ring, 11
  - segment, scalability of, 59
  - in star topology, 56
  - Token Ring and, 141, 144
    - bridging, 11, 142
  - transceivers, 140
  - (see also Ethernet II; Fast Ethernet; Gigabit Ethernet; 10 Gigabit Ethernet)
- Ethernet II, 7, 142
- Ethertype, 133
- ETR (Early Token Release), 143
- Expedited Forwarding (see EF)
- Extended Service Set (ESS), 156
- Exterior Gateway Protocol (see EGP)

## F

- failures, 15
  - cost efficiency and, 15, 23
  - dynamic routing protocols and, 193
  - hard, 45
  - modes, 44–49
    - congestion, 45
    - human error, 49

- software problems, 48
- traffic anomalies, 47
- MTBF, 36
  - combining values, 39–44
- multiple simultaneous, 23
  - MTBF and, 37–39
- predicting, 35–44
- probability of, 23, 45
- single point of
  - collapsed backbones, 73
  - isolating, 31–35
  - star topologies, 57
- trunk, Spanning Tree, 64
- Fair Queuing, 259
- Fast Ethernet, 6, 57, 130–141
  - bridges/hubs/switches, 139
  - bridging through, 142
  - collapsed backbones, 72
  - cost efficiency, 127
  - distributed backbones, 76
  - Gigabit Ethernet and, 146
  - physical implementations, 130
  - switching
    - modern style routing vs., 81
    - strategies, 96
- fault management, 274
  - information, hubs and, 128
- fault recovery, automated, 24–30
  - examples of, 27–30
  - intrinsic vs. external, 26
  - for large-scale networks, 61–66
    - Spanning Tree, 61–65
  - Layer 3, 65
  - OSPF, 65
- fault recovery, manual, 30
- fault tolerance, 14, 24–30
  - bus topology, 55
  - distributed backbones, 77
  - via load balancing, 28–30
  - ring topology, 55
  - star topologies, 57
    - (see also fault recovery, automated)
- FCS (Frame Check Sequence), 134
- FDDI (Fiber Distributed Data Interface), 6, 55, 154
  - collapsed backbones, 71
- Fiber Distributed Data Interface (see FDDI)
- fiber optic, 131
  - Fast Ethernet/Gigabit Ethernet, 146
- Fiber Optic Inter-Repeater Link (FOIRL), 131
- FIFO (First In First Out), 257, 259

- File Transfer Protocol (see FTP)
- filtering, 275
  - application control, 94
  - efficiency and, 253
  - ICMP and, 254
  - IPX, 93
  - network-management problems with, 293
  - policy-based routing, 94
  - RIP, 237
  - routing strategies, 92–95
  - SAP and, 237, 253
  - security and, 92, 337
  - switching strategies, 99
- firewalls, 275
  - IP addressing and, 178
  - LANs and, 160–162
  - network-management problems
    - with, 294–296
  - routers as, 161
  - wireless LANs and, 159
- First In First Out (see FIFO)
- floating static routes, 195
- flooding, 215
- flows, 91, 261
- FOIRL (Fiber Optic Inter-Repeater Link), 131
- forward delay timer (Spanning Tree), 64
- Frame Check Sequence (FCS), 134
- Frame Relay WAN links, ATM and, 151
- framing standards, Ethernet, 132–136
  - addresses, 135
- frequency, 255
- FTP (File Transfer Protocol), 8
  - IP traffic classification fields, 267
  - presentation layer and, 8
  - queuing and, 259
- full-duplex
  - access, collision detection and, 137
  - connections, end devices to Gigabit Ethernet, 147
  - transmission, trunks and, 76
- fully meshed topology, 57

## G

- gateways
  - default, 190
  - LANs and, 160–162
  - proxy host, 161
  - web proxy, 161
- Gigabit Ethernet, 146–149
  - as backbone protocol, 148
  - bottlenecks and, 253

Gigabit Ethernet (*continued*)

- bridging through, 142
- on desktops, 147
- Fast Ethernet and, 146
- signaling standards for, 146
- Gigabit Media Independent Interface (GMII), 146
- globally unique address (GUA), 234
- GMII (Gigabit Media Independent Interface), 146
- GUA (globally unique address), 234
- Guaranteed Delivery, 256
- VLL and, 257

## H

- hard failures, 45
- hello timer (Spanning Tree), 64
- hops
  - hop counts, 249
  - PHB and, 261
- horizontal cabling, 163–166
- Hot Standby Router Protocol (see HSRP)
- HSRP (Hot Standby Router Protocol), 65
  - collapsed backbones, 74
  - redundancy, 88
- HTTP (Hypertext Transfer Protocol)
  - queuing and, 259
  - security and, 334
- hub and spoke topology, 56
- hubs, 56
  - 10/100, 140
  - augmenting access level with, 128
  - bus topology and, 55
  - design issues, 139
  - fault-management information and, 128
  - security and, 336
  - switches vs., 95
- Hypertext Transfer Protocol (see HTTP)

## I

- IBM protocols on Token Ring segments, 251
- ICMP (Internet Control Message Protocol), 176
  - filtering and, 254
  - ping, 69, 284
  - Redirect message, 176
- IEEE 802.1d (see Spanning Tree)
- IETF (Internet Engineering Task Force), 169
  - queuing standards, 261
- IGMP (Internet Group Management Protocol), 310–311

- IGP (Interior Gateway Protocol), 196, 223
- IGRP (Interior Gateway Routing Protocol), 206–213
  - (see also EIGRP)
- installed base, 3
  - cost efficiency, 129
  - LAN technologies, 129
- instance managers (SNMP), 286
- Integrated Services (see IS)
- Interior Gateway Protocol (see IGP)
- Intermediate System to Intermediate System (IS-IS), 239
- Internet, 170
  - routing, 174
  - routing protocols and, 229
- Internet Control Message Protocol (see ICMP)
- Internet Engineering Task Force (IETF), 169
- Internet Group Management Protocol (see IGMP)
- Internet Protocol (see IP)
- Internetwork Packet Exchange (see IPX)
- intserv (see IS)
- inverse terminal server, polling serial devices
  - with, 303
- IP ARP packets, 48
- IP dynamic routing, 193–233
  - BGP (see BGP)
  - IGRP/EIGRP (see IGRP; EIGRP)
  - OSPF (see OSPF)
  - RIP (see RIP)
  - types of protocols, 196
- IP (Internet Protocol), 7, 169–192
  - addressing, 170–175, 177, 182–191
    - classes, 173–175
    - default gateways, 190
    - flexibility, 189
    - loopbacks, 188
    - for OSPF, 224
    - ranges, 184–187
    - standard subnet masks, 187–189
    - unregistered addresses, 182
  - all-subnets broadcast, 180
  - ARP and, 175
  - Classical IP, 152
  - DHCP and, 191
  - DNS and, 191
  - dynamic routing (see IP dynamic routing)
  - hop counts, 249
  - ICMP and, 176
  - IPX and, 7
    - comparison, 234



- multiple subnet broadcast, 179–181
- NAT and, 177–179
- precedence values, 264
- routing, 11
- traffic classification fields, 267
- VLANs and, 66, 69
- (see also IP multicast networks)
- IP multicast networks, 306–318
  - addressing, multicast, 307
  - design considerations, 315–318
    - multicast administrative zones, 316–318
    - QoS and, 318
  - group membership, 312
  - IGMP, 310–311
  - multicast routing, 313–315
    - BGMP and, 315
    - DVMRP, 314
    - MOSPF, 313
    - PIM and, 315
  - services, 308–310
- IPsec, 338
- IPv4 (see IP)
- IPv6, 319–333
  - addressing, 322–325
    - allocations, 324
  - autoconfiguration, 327–328
  - header structure, 320–322
  - IPv4 to IPv6, migrating, 331–333
  - multicast and anycast, 329–331
  - QoS, 325
  - security, 326
  - (see also IP)
- IPX (Internetwork Packet Exchange), 7, 169, 234–246
  - addressing, 242–244
  - design strategies, 242–246
    - efficiency, 245
    - RIP and SAP accumulation zones, 244
  - dynamic routing, 236–242
    - EIGRP, 238
    - NLSP, 239–242
    - RIP and SAP, 236–238
  - Ethernet types, 133
  - filtering and, 93, 253
  - hop counts, 249
  - IP and, 7
    - comparison, 234
  - merging networks, 235
  - VLANs and, 66

- IS (Integrated Services), 261–263
  - design considerations, 270
- IS-IS (Intermediate System to Intermediate System), 239

## J

- jamming pattern (Ethernet), 137
- jitter, 250, 255

## L

- LAA (Locally Administered Address), 132, 135
- labeling, patch panels and cords, 277
- LAN Emulation Client (LEC), 153
- LAN Emulation Configuration Server (LECS), 153
- LAN Emulation (see LANE)
- LAN Emulation Server (LES), 153
- LANE (LAN Emulation), 149, 152
  - SVCs and, 150
- late collision, 137
- latency, 16
  - bandwidth and, 255
  - hop counts and, 250
  - jitter, 250, 255
  - MTU and, 251
  - routers vs. switches, 83
- Layer 3 switches, 10, 84–87
  - routing vs., 11
- LEC (LAN Emulation Client), 153
- LECS (LAN Emulation Configuration Server), 153
- LES (LAN Emulation Server), 153
- Link State Advertisement (LSA), 216
- Link State algorithm, 213, 236
- Link State information, 213
  - NLSP, 239
- LLC (Logical Link Control), 134
- load balancing, 28–30
  - distributed backbones, 78
- Locally Administered Address (see LAA)
- Logical Link Control (LLC), 134
- logs, monitoring, 283
- LSA (Link State Advertisement), 216

## M

- MAC addresses, 54, 132, 135
  - ARP and, 175
  - broadcast/multicast, 135

MAC addresses (*continued*)  
 DECNET protocol, 135  
 fault recovery and, 27  
 IP ARP packets and, 48  
 multicast IP addresses, converting  
   between, 307  
 security and, 99  
 updating, 63  
 MAC (Media Access Control), 11  
 MADCAP protocol, 309  
 maintenance  
   LAN technologies, 129  
   redundancy and, 18  
 MAN (Metropolitan Area Network), 3  
   Gigabit Ethernet as backbone on, 149  
 manageability  
   cost efficiency, 12  
   redundancy, implementing, 23  
   VLANs, 67  
   (see also network management)  
 Management Information Base (see MIB)  
 MAU (Media Attachment Unit—see hubs)  
 maximum age timer (Spanning Tree), 64  
 Maximum Transmission Unit (see MTU)  
 MBONE (multicast backbone), 315  
 Mean Time Between Failures (see MTBF)  
 Media Access Control (MAC), 11  
 Media Attachment Unit (MAU—see hubs)  
 mesh topology, 57  
 metrics (RIP), 199  
 Metropolitan Area Network (see MAN)  
 MIB (Management Information Base), 281  
   extensions  
     monitoring networks, 286  
     for Spanning Tree, monitoring, 297  
 MMUSIC (Multiparty Multimedia Session  
   Control Working Group), 312  
 modems, out-of-band management of, 298  
 monitoring, 281–286  
 MOSPF (Multicast OSPF), 313  
 MPOA (Multiple Protocol Over ATM), 152  
 MTBF (Mean Time Between Failures), 36  
   combining values, 39–44  
   multiple simultaneous failures and, 37–39  
 MTU (Maximum Transmission  
   Unit), 250–252  
   mismatch problems, 250  
   Path MTU Discovery process, 251  
 multicast address, 135  
 multicast backbone (MBONE), 315  
 Multicast OSPF (MOSPF), 313

Multiparty Multimedia Session Control  
   Working Group (MMUSIC), 312  
 Multiple Protocol Over ATM (MPOA), 152

## N

NAT (Network Address Translation), 161,  
   177–179  
   SNMP and, 179  
 NBAR (Network-Based Application  
   Recognition), QoS classes and, 268  
 NBMA (Nonbroadcast Multiple Access), 216  
 NetBEUI, 169  
 netmasks, 170, 171  
   standard, for common uses, 187–189  
 Network Address Translation (see NAT)  
 network devices, 53  
   automated fault recovery and, 26  
   design philosophy and, 13  
   Ethernet framing standards, 132  
   redundancy and, 18  
   stability and, 31  
 Network Interface Cards (see NIC)  
 network layer (OSI model), 7  
   protocols commonly in use, 169  
   VLANs and, 21  
 network management, 273–305  
   accounting management, 275  
   capacity planning, 275  
   configuration management, 273  
     tracking physical changes, 274  
   dedicated equipment for, location of, 279  
   design considerations, 275–280  
     ease of access, 277  
     equipment, location of, 279  
   fault management, 274  
   out-of-band techniques, 298–305  
   performance management, 274  
     SNMP and, 283  
   problems with, 288–305  
     backups, 296  
     DHCP, 289  
     filtering, 293  
     firewalls, 294–296  
     LAN extension, 292  
     nonstandard devices, 302  
     redundancy, 296  
     tunnels, 297  
     VLAN structures, 291–292  
   security management, 275  
   SNMP, 280–288  
     monitoring with, 281–286

network number, 234  
 Network Operating System (see NOS)  
 Network-Based Application Recognition (NBAR), QoS classes and, 268  
 Network-Network Interface (NNI), 150  
 NIC (Network Interface Card), 132  
     multiple, 53  
     stability and, 51  
 NLSP (Novell Link State Protocol), 235, 239–242  
     areas, 239  
     routing, 241  
 NNI (Network-Network Interface), 150  
 Nonbroadcast Multiple Access (NBMA), 216  
 nontransit areas, 217  
 NOS (Network Operating System), 7, 234  
 Not-So-Stubby area (NSSA), 217  
 Novell Link State Protocol (see NLSP)  
 Novell Network Registry, 235  
 NSSA (Not-So-Stubby Area), 217

## O

objectives, 1  
     reliability, 247  
 one-armed routers, 84–87  
 Open Shortest Path First (see OSPF)  
 Organizationally Unique Identifier (OUI), 135  
 OSI model, 5–10  
     application layer, 9  
     breakdown of, 9  
     data link layer, 6  
         network congestion and, 47  
     layers of, 5–9  
     network layer, 7  
         VLANs and, 21  
     physical layer, 6  
     presentation layer, 8  
     session layer, 8  
     transport layer, 7  
 OSPF (Open Shortest Path First), 84, 213–228  
     areas, 185, 188, 215  
         structures, 219–222  
         types of, 217–219  
     Autonomous Systems, 185, 215  
         interconnecting, 222  
     bottlenecks and, 253  
     costs, 225–228  
     end devices and, 53  
     fault recovery, automated, 65  
     interconnecting Autonomous Systems, 222

IP-addressing schemes for, 224  
 redistributing with other routing protocols, 223  
 traffic anomalies, 47  
     resolving, 48  
 OUI (Organizationally Unique Identifier), 135  
 out-of-band network-management techniques, 298–305

## P

Packet Description Language Module (PDL), QoS classes and, 268  
 packets  
     ARP, broadcast address, 136  
     buffering, 266  
     Drop Precedence, 262  
     dropped, 256  
     fragmentation, 250  
     hop counts and, 249  
     IP ARP, 48  
     latency and (see latency)  
     policing, 266  
     prioritizing, 249  
     SAP, filtering and, 253  
     size of, QoS classes and, 268  
     TTL field, 202  
 partially meshed topology, 57  
 patch panels, 277  
     IBDN, 57  
 Path MTU Discovery process, 251  
 PDL (Packet Description Language Module), QoS classes and, 268  
 PDU (Protocol Data Unit), 134  
 peer-to-peer networks, collapsed backbones, 70  
 performance, 16–17  
     cost efficiency and, 16, 127  
     LAN technologies, 130  
     management, 274  
     SNMP and, 283  
     peak load, 14  
     (see also efficiency)  
 Per-Hop Behavior (see PHB)  
 Permanent Virtual Circuit (PVC), 150  
 PHB (Per-Hop Behavior), 261  
     AF and EF, 261  
 physical layer (OSI model), 6  
 PIM (Protocol Independent Multicast), 315  
 ping, 176  
     for monitoring, 284  
     VLANs and, 69  
 PNNI (Private Network-Network Interface), 150

- point-to-point circuits, 6
- point-to-point protocol (see PPP)
- policing, 266
- polling, 281
- port numbers, 8
  - QoS classes and, 268
  - TCP/UDP, filtering for security, 93
- ports
  - blocking, 62
  - console, management problems with, 305
  - forwarding state, 63
  - LAN, out-of-band management and, 300
  - learning state, 63
  - monitoring utilization, 283
  - serial, out-of-band management and, 300  
(see also port numbers)
- PPP over Ethernet (PPPoE), 9
- PPP (point-to-point protocol), 155
  - out-of-band management and, 300
- PPPoE (PPP over Ethernet), 9
- Preferential Delivery, 256
  - Priority Queuing, 260
  - Weighted Fair Queuing and, 259
- presentation layer (OSI model), 8
- Priority Queuing, 260
- Private Network-Network Interface (PNNI), 150
- probabilities, combining, 341–343
- probes, location of, 275
- Protocol Data Unit (PDU), 134
- Protocol Independent Multicast (PIM), 315
- protocol stack model (see OSI model)
- protocols
  - analyzers, network management and, 291
  - congestion and, 46
  - dynamic routing
    - end devices and, 53
    - fault recovery, automated, 65
    - Internet and, 229
    - types of, 196  
(see also IP dynamic routing; OSPF; RIP)
  - IBM run on Token Ring segments, 251
  - MADCAP, 309
  - network layer, commonly used, 169
  - routable/nonroutable, 169
  - VLANs based on, 68
- proxy
  - ARP, 25
  - host, 161
- PVC (Permanent Virtual Circuit), 150

## Q

- QoS (Quality of Service), 256–258
  - ATM and, 151
  - classes, 267
  - congestion and, 252
  - design considerations, 270–272
  - DSCP and TOS, 263–265
  - implementing, 249
  - Integrated and Differentiated Services, 261–263
  - IP multicast networks and, 318
  - IPv6 and, 325
  - Layers 2 and 3, 258
  - RSVP and, 269
  - traffic shaping and, 266
  - traffic shaping (see traffic, shaping)
- Quality of Service (see QoS)
- queues
  - monitoring statistics about, 286
  - polling and, 282  
(see also queuing)
- queuing, 258–261
  - Fair Queuing, 259
  - FIFO, 259
  - Priority Queuing, 260
  - Weighted Fair Queuing, 257, 259

## R

- Random Early Detection (RED), 252
- RED (Random Early Detection), 252
- redundancy, 17–44
  - ATM, 153
  - BUS/LECS/LES servers, 153
  - collapsed backbones, 73
  - complexity and manageability, 23
  - core-level routers, 116
  - cost efficiency, 42
  - distributed backbones, 77
  - failures
    - hard, 45
    - modes, 44–49
    - MTBF, 36, 39–44
    - multiple simultaneous, 23, 37–39
    - predicting, 35–44
    - probability of, 45
    - single point of, 31–35
  - fault recovery, automated, 24–30
  - examples of, 27–30
  - intrinsic vs. external, 26

- implementing, 18–20
  - backups, 19
  - duplicating equipment, 19
- network-management problems with, 296
- by protocol layer, 21–23
- routing strategies, 88–92
  - physical diversity, 90–92
  - router-to-router segments, 88–90
- Spanning Tree, multiple connections, 115
- switching strategies, 98
- reliability, 14, 26
  - failures and, 15
  - Gigabit Ethernet, 146
  - implementing, 113–115
    - multiple connections, 114
  - networks as end devices, 53
  - TCP/UDP and, 7
  - (see also fault recovery, automated; fault tolerance; performance)
- Remote Procedure Call (RPC) applications,
  - QoS classes and, 268
- Request for Comment (RFC), 169
- requirements
  - business, 1–4, 16
    - bandwidth (see bandwidth)
    - expenses, 2
    - geography, 2
    - installed base, 3
    - security (see security)
    - vs. technical, 1
  - philosophical, 4
  - user, 17
- Reservation Protocol (see RSVP)
- RFC (Request for Comment), 169
- ring topology, 55
- RIP (Routing Information Protocol—IP), 25,
  - 84, 197–206
  - end devices and, 53
  - functionality, 199–201
  - loops, avoiding, 202–204
  - metrics, 199
  - redistributing with other protocols, 206
  - split horizons in, 204
  - variable subnet masks, 205
- RIP (Routing Information Protocol—IPX), 236–238
  - accumulation zones, 244
  - avoiding, 245
  - EIGRP and, 238
- roaming (wireless LANs), 156
- root bridges, 62
- route tags
  - EIGRP, 212
  - RIP, 206
- routers, 83, 234
  - backbone, 219
  - border, 213
  - bugs in, 48
  - core-level, 116–118
    - redundancy, 116
  - distribution-level, 118
  - efficient use of, 248
  - fault recovery, automated, 27
    - as firewalls, 161
  - flows, 91
  - as gateways, 161
  - ICMP Redirect message, 176
  - installing, 84
  - latency, 83
  - monitoring, 284
    - buffering and queuing statistics, 286
  - multilevel, 119
  - NLSP and, 239
  - one-armed, 84–87
  - physical diversity, 90–92
  - queuing and, 255
  - redundancy and, 25
  - remote sites, connecting, 121–124
  - router-to-router segments, 88–90
    - as single points of failure, 31
  - TCP/IP and, 161
  - trunking through, 102–104
    - (see also routing; routing strategies)
- routing
  - ATM and, 11
  - bottlenecks and, 253
  - bridging vs., 10–12
  - classless, 228
  - Internet, 174
  - IP dynamic (see IP dynamic routing)
  - multicast, 313–315
    - BGMP, 315
    - DVMRP, 314
    - MOSPF, 313
    - PIM, 315
  - policy-based, 94
  - stability and, 51
  - static, 194–196
    - floating static routes, 195
  - switching vs., 78–81
    - modern design, 80
    - old-style design, 78–80
    - (see also Layer 3 switches; routing strategies)

Routing Information Protocol (see RIP)

routing loops, 194

avoiding, 202–204

routing strategies, 83–95

filtering, 92–95

for application control, 94

policy-based routing, 94

for security, 92

Layer 3 switches, 84–87

one-armed routers, 84–87

redundancy, 88–92

physical diversity, 90–92

router-to-router segments, 88–90

routing tables, 193, 199

RPC (Remote Procedure Call) applications,

QoS classes and, 268

RSVP (Reservation Protocol), 261

efficiency and, 270

QoS and, 269

## S

SAP (Service Advertisement Protocol), 136, 236–238

accumulation zones, 244

avoiding, 245

scalability

congestion and, 47

of Ethernet segment, 59

meshed topologies and, 58

routing vs. bridging, 11

of topologies, 58–61

security, 4, 333–340

filtering and, 92, 337

switching strategies, 99

firewalls, 161

hub and switch port-level security, 336

IPsec and, 338

IPv6 and, 326

management, 275

out-of-band, 299

password recovery, 305

routers and, 52, 84

SNMP and, 280, 286, 296

VLANs and, 69

VPNs and, 9

wireless LANs and, 158–159

(see also firewalls; gateways)

Sequenced Packet Exchange (SPX), 236

Serial Line Internet Protocol (SLIP),

out-of-band management and, 300

servers

BUS, 153

DNS, linking to DHCP servers, 289

inverse terminal, polling serial devices  
with, 303

LECS, 153

LES, 153

NetWare, 234

network-management monitoring, 284

NLSP and, 239

routers as, 53

SNMP, 280

Service Advertisement Protocol (see SAP)

Service Advertisement table, IPX and, 242

session layer (OSI model), 8

signaling, baseband/broadband, 131

Simple Network Management Protocol (see  
SNMP)

single point of failure

collapsed backbones, 73

star topologies, 57

single-ring topology, 55

SLIP (Serial Line Internet Protocol),

out-of-band management and, 300

SNA (Systems Network Architecture), 8, 169

SNAP (Sub-Network Access Protocol), 134

SNMP (Simple Network Management  
Protocol), 179

agents/servers, 280

monitoring with, 281–286

ad hoc queries, 286

automated activities, 287

instance managers, 286

items to monitor, 285

Spanning Tree, 297

sysUpTime, 285

network management and, 280–288

security and, 280, 286, 296

soft expense, 15

software problems (see bugs in  
routers/switches)

SONET, 55

source-route bridging, 145

spaghetti factor, 68

Spanning Tree, 61–65

backup links/devices, activating, 63–65

collapsed backbones, 74

loops, eliminating, 62

multiple connections, 115

network-management problems with, 291

SNMP monitoring of, 297

- timers, 64
  - values, 64
- traffic anomalies and, 47
- trunk failures, 64
- trunk redundancy, 107
- Split Horizon algorithm, 205
  - Split Horizon with Poisoned Reverse, 208
- SPX (Sequenced Packet Exchange), 236
- stability
  - analyzing, 31–35
  - end devices and, 51
  - redundancy and, 45
  - single points of failure and, 31
- star topology, 56
- static routing, 194–196
  - floating static routes, 195
- STP (Spanning Tree Protocol—see Spanning Tree)
- structured cabling, 162–168
  - horizontal, 163–166
  - vertical, 166
- stub areas, 217
- subnets, 171
  - counting from the left scheme, 172
  - masks, 171
    - standard, for common uses, 187–189
  - variable subnet masks, 205
  - (see also IP)
- Sub-Network Access Protocol (SNAP), 134
- SVC (Switch Virtual Circuit), 150
- switches
  - augmenting access level with, 128
  - bugs in, 48
  - bus topologies and, 55
  - design issues, 139
  - distribution, 64
  - fault-management information and, 128
  - hubs vs., 95
  - latency, 83
  - Layer 3, 84–87
    - routing vs., 11
  - monitoring, 284
  - redundant core, 64
  - security and, 336
  - as single points of failure, 31
  - (see also switching)
- switching
  - Layer 3, 10
  - routing vs., 78–81
    - modern design, 80
    - old-style design, 78–80
  - store-and-forward, 11

- strategies, 95–100
  - broadcasts and, 96–98
  - filtering, 99
  - redundancy, 98
  - (see also bridging)
- Systems Network Architecture (see SNA)

## T

- TCP (Transmission Control Protocol), 7
  - congestion and, 46
  - DF bit, 251
  - IP traffic classification fields, 267
  - NAT and, 179
  - packets, dropping, 266
- TCP/IP
  - bridging through Fast or Gigabit Ethernet segments, 142
  - DECNET operating with, 135
  - Ethernet types, 133
  - routers and, 161
  - (see also IP)
- telephony, ATM and, 149, 151
- telnet, 8
- thick-net, 131
- thin-net (see 10Base2)
- throughput, 10BaseT hub, 60
- Time To Live (TTL), 202
- token, 143
  - bus topology, 54
  - mesh topology, 57
  - ring topology, 55
  - star topology, 56
- Token Ring, 6, 55, 141, 141–145
  - ATM compared to, 153
  - collapsed backbones, 74
  - collision rates, 60
  - congestion and, 47
  - cost efficiency, 126, 144
  - Ethernet and, 141, 144
    - bridging, 11, 142
  - ETR, 143
  - IBM protocols on, 251
  - MTU default, 250
  - QoS, Layer 2, 258
  - routing, IP from Ethernet, 11
  - scalability, 59
  - in star topology, 56
  - VLANs, 145
- topologies, 54–58
  - bus, 54
  - hub and spoke, 56

topologies (*continued*)

- LAN, large-scale, 115–125
  - core-level routers, 116–118
  - distribution-level routers, 118
  - remote sites, connecting, 121–124
- large-scale, 70–81
  - collapsed backbones, 70–74
  - distributed backbone, 74–78
  - multilevel routers, 119
  - switching vs. routing, 78–81
  - (see also topologies, LAN, large-scale)
- mesh, 57
- ring, 55
- scalability of, 58–61
- star, 56
- token bus, 54
- TOS (Type of Service), 263–265
- totally stub areas, 217
- traceroute, VLANs and, 69
- traffic, 4
  - anomalies, 47
  - congestion, 46
  - Ethernet segment and, 59
  - hierarchical design, 83
  - human error and, 49
  - IP classification fields, 267
  - shaping, 265
  - types, defining, 267–268
  - (see also bandwidth; congestion)
- transceivers, 140
  - out-of-band management of, 298
- Transit areas, 217
- Transmission Control Protocol (see TCP)
- transmission, full-duplex, trunks and, 76
- transport layer (OSI model), 7
- traps, 280
  - logs, monitoring, 283
- trouble tickets, automated, 283
- troubleshooting
  - fault management and, 274
  - VLANs, 67
- trunks, 75, 104–110
  - capacity, distributed backbones, 75–77
  - congestion and, 47
  - cost efficiency, 109
  - design, 100–102
  - failures, Spanning Tree, 64
  - fault tolerance, distributed backbones, 77
  - probes on, 276
  - trunking through router, 102–104
  - VLANs and, network-management problems with, 291–293

TTL (Time To Live), 202

tunnels

- management of
  - out-of-band, 299
  - problems with, 297
- OSI model and, 9
- Type 3 cabling, 6
- Type of Service (see TOS)

**U**

- UBR (Unspecified Bit Rate), 151
- UDP (User Datagram Protocol), 7
  - packets, dropping, 266
  - Path MTU Discovery process and, 251
- UNI (User-Network Interface), 150
- unicasts, 54
- Unshielded Twisted Pair (UTP), 146
- Unspecified Bit Rate (UBR), 151
- User Datagram Protocol (see UDP)
- User-Network Interface (UNI), 150
- users
  - locations of, 2
  - requirements of, 17
- UTP (Unshielded Twisted Pair), 146

**V**

- Variable Bit Rate (VBR), 151
- Variable Length Subnet Masks (VLSM), 206
- VBR (Variable Bit Rate), 151
- VC (Virtual Circuit), 150
- VCI (Virtual Channel Identifier), 150
- vertical cabling, 166
- Virtual Channel Identifier (VCI), 150
- Virtual Circuit (VC), 150
- Virtual LAN (see VLAN)
- Virtual Leased Line (see VLL)
- Virtual Path Identifier (VPI), 150
- Virtual Private Network (see VPN)
- Virtual Router Redundancy Protocol (see VRRP)
- VLAN (Virtual LAN), 3, 21, 66–70
  - cost efficiency, 66
  - IP addressing and, 186
  - management VLANs, dedicated, 276
  - probes and, 275
  - protocol-based, 68
  - spaghetti, avoiding, 67–68
  - subnet masks, 187
  - Token Ring switches, 145
  - topologies based on, 100–113
    - distribution areas, 110–113



- trunking through router, 102–104
- trunks, 100–110, 276, 291–293
- VLL (Virtual Leased Line), 257
  - EF and, 263
- VLSM (Variable Length Subnet Masks), 206
- VPI (Virtual Path Identifier), 150
- VPN (Virtual Private Network), 9
  - wireless LANs and, 159
- VRRP (Virtual Router Redundancy Protocol), 65
  - collapsed backbones, 74
  - redundancy, 88

## W

- WAN (Wide Area Network), 3
  - ATM and, 149
  - congestion and, 47
  - Gigabit Ethernet as backbone on, 149
  - LANE and, 149
  - latency and, 255
  - polling on, 282
  - PVCs and, 150
- web proxy, 161
- Weighted Fair Queuing, 257, 259
- WEP (Wired Equivalent Privacy), 158
- Wide Area Network (see WAN)
- Wired Equivalent Privacy (WEP), 158
- wireless LANs, 155–159

