

➤ **Vendor: Microsoft**

➤ **Exam Code: 70-741**

➤ **Exam Name: Networking with Windows Server 2016**

➤ **New Questions (Mar/2019)**

[Visit PassLeader and Download Full Version 70-741 Exam Dumps](#)

**NEW QUESTION 234**

You have a Hyper-V host named Server 1. The network adapters on Server1 have single root I/O virtualization (SR-IOV) enabled. Server1 hosts a virtual machine named VM1 that runs Windows Server 2016. You need to identify whether SR-IOV is used by VM1.

Solution: You sign in to VM1. You run the Get-NetAdapterSriov cmdlet.

Does this meet the goal?

- A. Yes
- B. No

**Answer: A**

**Explanation:**

<https://docs.microsoft.com/en-us/powershell/module/netadapter/get-netadaptersriov?view=win10-ps>

**NEW QUESTION 235**

You have a Hyper-V host named Server 1. The network adapters on Server1 have single root I/O virtualization (SR-IOV) enabled. Server1 hosts a virtual machine named VM1 that runs Windows Server 2016. You need to identify whether SR-IOV is used by VM1.

Solution: You sign in to VM1. You view the properties of the network connections.

Does this meet the goal?

- A. Yes
- B. No

**Answer: B**

**NEW QUESTION 236**

You have a Hyper-V host named Server 1. The network adapters on Server1 have single root I/O virtualization (SR-IOV) enabled. Server1 hosts a virtual machine named VM1 that runs Windows Server 2016. You need to identify whether SR-IOV is used by VM1.

Solution: On Server1, you open Hyper-V Manager and view the Integration Services settings of VM1.

Does this meet the goal?

- A. Yes
- B. No

**Answer: B**

**NEW QUESTION 237**

You have a Hyper-V host named Server 1. The network adapters on Server1 have single root I/O virtualization (SR-IOV) enabled. Server1 hosts a virtual machine named VM1 that runs Windows Server 2016. You need to identify whether SR-IOV is used by VM1.

Solution: You sign in to VM1. You open Device Manager and view the properties of the network adapters.

Does this meet the goal?

- A. Yes
- B. No

**Answer: B**

**NEW QUESTION 238**

Your network contains an Active Directory domain named contoso.com. The domain contains a server named Server2 that runs Windows Server 2016. The DHCP Server server role is installed on Server2. The DNS server role is installed on a server named Server3. The network contains 500 non-Windows devices that are registered in the DNS zone of contoso.com. You configure Server2 to lease IP addresses to the non-Windows devices. You need to prevent Server2 from overwriting the host (A) records for the non-Windows devices. What should you run?

- A. `dism.exe`
- B. `dns.exe`
- C. `dnscmd.exe`
- D. `netsh.exe`
- E. `Set-DhcpServerDatabase`
- F. `Set-DhcpServerv4DnsSetting`
- G. `Set-DhcpServerv6DnsSetting`
- H. `Set-DNSServerSetting`

**Answer: C**

**Explanation:**

<https://docs.microsoft.com/en-us/windows-server/administration/windows-commands/dnscmd>

**NEW QUESTION 239**

You have a server named Server1 that runs Windows Server 2016. Server1 is an IP Address Management (IPAM) server that collects DHCP and DNS logs and events for your entire network. You need to enable a user named TECH1 to create pointer (PTR), host (A) and service location (SRV) records on all of the DNS servers on the network. What should you do on Server1?

- A. Run the `Set-IpamRange` cmdlet, and then run the `Set-IpamAddressSpace` cmdlet.
- B. Run the `Set-IpamCustomField` cmdlet, and then run the `Set-IpamAccessScope` cmdlet.
- C. From the IPAM node in Server Manager, assign the IPAM DNS Administrator Role to TECH1 and create a new access policy.
- D. From the IPAM node in Server Manager, assign the IPAM DNS Administrator Role to TECH1 and create a new access scope.

**Answer: D**

**Explanation:**

<https://docs.microsoft.com/en-us/windows-server/networking/technologies/ipam/view-roles-and-role-permissions>

**NEW QUESTION 240**

You have a server named Server1 that has a Server Core installation of Windows Server 2016. Server1 is configured to obtain an IP address automatically. You need to configure the IPv4 address, netmask, and default gateway manually for a network interface named Ethernet on Server1. What should you run?

- A. ipconfig.exe
- B. New-NetIPAddress
- C. Set-NetAdapter
- D. Set-NetIPv4Protocol

**Answer: B**

**Explanation:**

<https://docs.microsoft.com/en-us/powershell/module/nettcpip/new-netipaddress?view=win10-ps>

**NEW QUESTION 241**

**Drag and Drop**

Your network contains an Active Directory domain named contoso.com. The domain contains two servers named Server1 and Server2 that run Windows Server 2016. Server1 has IP Address Management (IPAM) installed. Server2 has Microsoft System Center 2016 Virtual Machine Manager (VMM) installed. You need to integrate IPAM and VMM. Which types of objects should you create on each server? (To answer, drag the appropriate object types to the correct servers. Each object type may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to view content.)

**Objects**

Access Policy	Network Service	Run As Account
Service Template	User Role	

**Answer Area**

Object to create on Server1:	
Object to create on Server2:	

**Answer:**

**Objects**

	Network Service
Service Template	

**Answer Area**

Object to create on Server1:	Run As Account
Object to create on Server2:	Access Policy    User Role

**Explanation:**

[https://technet.microsoft.com/en-us/library/dn783349\(v=ws.11\).aspx](https://technet.microsoft.com/en-us/library/dn783349(v=ws.11).aspx)

**NEW QUESTION 242**

**Hotspot**

You use a Network Policy Server (NPS) server named NPS1 to authenticate VPN connections and connections to wireless access points (WAPs). You plan to add a new WAP named WAP1. What should you do on WAP1 and NPS1? (To answer, select the appropriate options in the answer area.)

**Answer Area**

Setting to configure on WAP1:

	▼
802.1X certificate	
Encryption protocol	
RADIUS server	
SSID	

Object to create on NPS1:

	▼
a connection request policy	
a network policy	
a RADIUS client	
a remote RADIUS server group	

**Answer:**

**Answer Area**

Setting to configure on WAP1:

	▼
802.1X certificate	
Encryption protocol	
RADIUS server	
SSID	

Object to create on NPS1:

	▼
a connection request policy	
a network policy	
a RADIUS client	
a remote RADIUS server group	

**Explanation:**

[https://docs.microsoft.com/en-us/windows-server/networking/core-network-guide/cncg/wireless/e-wireless-access-deployment#bkmk\\_radiusclient](https://docs.microsoft.com/en-us/windows-server/networking/core-network-guide/cncg/wireless/e-wireless-access-deployment#bkmk_radiusclient)

**NEW QUESTION 243**

You have a server named Server1 that runs Windows Server 2016 and is configured as a domain controller. You install the DNS Server server role on Server1. You plan to store a DNS zone in a custom Active Directory partition. You need to create a new Active Directory partition for the zone. What should you use?

- A. Set-DnsServer
- B. Dns.exe
- C. Ntdsutil.exe
- D. Active Directory Administrative Center

**Answer: C**

**Explanation:**

<https://www.dell.com/support/article/za/en/zabsdt1/sln288363/how-to-create-a-custom-application-directory-partition-in-active-directory?lang=en>

**NEW QUESTION 244**

You are deploying a small network that has 30 client computers. The network uses the 192.168.1.0/24 address space. All computers obtain IP configurations from a DHCP server named Server1. You install a server named Server2 that runs Windows Server 2016. Server2 has two network adapters named Internal and Internet. Internet connects to an Internet Service Provider (ISP) and obtains the 131.107.0.10 IP address. Internal connects to the internal network and is configured to use the 192.168.1.250 IP address. You need to provide Internet connectivity for the client computers. What should you do?

- A. On Server2, select the Internet and Internal network adapters and bridge the connections. From the DHCP console on Server1, authorize Server2.
- B. On Server2 run the New-NetNat -Name NAT1 -InternalIPInterfaceAddressPrefix 192.168.1.0/24 cmdlet. Configure Server1 to provide the 003 Router option of 131.107.0.10.
- C. On Server1, stop the DHCP server. On the Internet adapter on Server2, enable internet Connection Sharing (ICS).
- D. Recreate the DHCP scope on Server1 to lease addresses from the 131.107.0.0/24 address space. On Server2, change the IP address of the internal network adapter to 131.107.0.1. Configure Server1 to provide the 003 Router option of 131.107.0.1.

**Answer: B**

**Explanation:**

<https://docs.microsoft.com/en-us/virtualization/hyper-v-on-windows/user-guide/setup-nat-network>  
<https://www.pctips3000.com/add-default-gateway-information-to-dhcp-in-windows-server-2008/>

**NEW QUESTION 245**

You have an Active Directory forest that contains 30 servers and 6,000 client computers. You deploy a new DHCP server that runs Windows Server 2016. You need to retrieve the list of the authorized DHCP servers. Which command should you run?

- A. Get-ADResourceProperty -Filter DHCP
- B. Netsh DHCP show server
- C. Netsh DHCP server initiate auth
- D. Get-DHCPServerSetting

**Answer: B**

**NEW QUESTION 246**

.....

[Visit PassLeader and Download Full Version 70-741 Exam Dumps](#)